






**Hidro
Pnevmo
Tehnika**

3, Vojeli St., Kazanlak, Bulgaria
Tel.: +359 431/ 62 228, 68 440
e-mail : info@hpt-bg.com
www.hpt-bg.com

VALVE BLOCKS

BV 99 / ..
(To be connected only to RS06...)



Note:

1. All performances and calibration are carried out by using hydraulic oil with viscosity approx 46 cSt at 50 °C.
2. Mounting plate:
 - acc. to ISO 4401-AB-03-4A (CETOP3)
3. Tightening torque of the connecting screws on the mounting plate - 8,5 N.m.

TECHNICAL DATA

General		
Ambient temperature	°C	-20...+50
Hydraulic		
Pressure range		See tab.1
Maximal flow rate	L/min	40
Working fluid- mineral oil		
- viscosity	mm ² /s	10...100
- filtration level	μm	25 or better
- temperature	°C	-20...80

Tab. 1

PRESSURE RANGE

Code	Standard setting (Q=5l/min) [bar]	Pressure range [bar]
10	80	10...100
25	180	30...250
35	250	70...350

This block is used only for a joint work with directional control valves of the RS06... type.

ORDERING CODE

BV 99 / 10

Type

Pressure range code:
see tab. 1